



PRODUCT SPECIFICATION REPORT

Liquid Brick
Grill & Oven Cleaner

8

Description:

Cleaner Solutions Liquid Brick is the most powerful combination of alkaline detergents, emulsifiers, and dispersants available on the market today. Specifically formulated for food service and restaurant industries, Liquid Brick will dissolve away even the thickest layers of built-up grease and cooking deposits from grills, ovens, grease filter ducts, and deep fryers.

Properties:

Form: Liquid
Fragrance: None
Appearance: Clear - Yellow

- ◆ **Removes Grease and Grease Build up.**
- ◆ **Decarbonizes.**
- ◆ **Economic.**
- ◆ **Low Fumes.**
- ◆ **Dilutable.**

Directions:

Ovens:

1. Set oven temperature between 180 and 200 degrees. Note: Product should not boil off the surface when applied.
2. Using the standard four to one dilution of Liquid Brick and a trigger foamer, apply a uniform coating of product to all surfaces. *Note: Use a Foaming Trigger Sprayer to keep fumes at a minimum.*
3. Allow the solution several minutes to work and then wipe clean with a wet towel. Inspect the oven for stubborn deposits and retreat as needed.

Deep Fat Fryers:

1. For weekly maintenance Liquid Brick may be diluted with as much as fifteen or twenty parts of water.
2. Add enough water to fryer to cover heating element and add sufficient Liquid Brick to achieve the desired dilution. Bring the solution to a boil and allow to simmer for at least three minutes. Heavier deposits may require as much as fifteen minutes of simmering or stronger concentrations of Liquid Brick.
3. Fill the fryer with water to the normal operating level, and place the fryer baskets and any other utensils that need cleaning into the hot solution. Allow to simmer until utensils and baskets are clean—usually five to ten minutes.
4. Drain the fryer and rinse it. Clean utensils in large amounts of fresh water.

Baking Racks and Burners:

1. Prepare a large, heavy-duty trash bag to insert baking racks or burners.
2. Dilute the Liquid Brick with ten parts of water.
3. Completely soak racks or burners and place the into the trash bag and seal the bag.
4. Let the items stand
5. Rinse all containers and racks thoroughly with large volumes of clean water before returning to service.

Caution: Liquid Brick contains Potassium Hydroxide. Do not allow this material to contact skin or eyes. Wear appropriate personal protective gear. Do not allow solutions to contact soft metals such as Zinc or Aluminum. Please refer to the MSDS for further precautions. Keep this and all similar materials out of the reach of children.

For spill, leak, or Medical Emergency call Infotrac 800-535-5053